

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 2000-002889

(43)Date of publication of application : 07.01.2000

(51)Int.Cl.

G02F 1/136

G09F 9/30

(21)Application number : 10-168175

(71)Applicant : MITSUBISHI ELECTRIC CORP

(22)Date of filing : 16.06.1998

(72)Inventor : NUMANO YOSHINORI

KAWAMOTO AKIRA


NAKAJIMA TAKESHI

(54) LIQUID CRYSTAL DISPLAY DEVICE

(57)Abstract:

PROBLEM TO BE SOLVED: To prevent the degradation in display quality, such as flickering occurring in the fluctuation with each of exposure regions, image persistence and display unevenness, by compensating the fluctuation in ΔC_{gd} by the fluctuation in C_{gd} generated with each of the exposure regions by changing a C_s value with each of the exposure regions.

SOLUTION: The C_{gd} changes when a drain electrode 8 deviates relatively in an x-axis direction D_x with respect to scanning wiring 2. If the drain electrode 8 deviates relatively in a $-x$ direction with respect to the scanning wiring 2, the overlap area of the drain electrode 8 and the scanning wiring 2 increases and the C_{gd} increases. Conversely, if the drain electrode 8 deviates relatively in a $+x$ direction with respect to the scanning wiring 2, the overlap area of the drain electrode 8 and the scanning wiring 2 decreases and the C_{gd} decreases. Then, the shapes of the drain electrode 8 and C_s wiring 3 in a B-B line part are so designed that $\Delta V_{gd} = (C_{gd} \times \Delta V_g) / (C_{gd} + C_s + C_{lc})$ is kept constant in spite of the fluctuation in the C_{gd} .



LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]

Copyright (C); 1998,2000 Japan Patent Office